



feed systems

***A complete
sodium hypochlorite
disinfection solution!***

PTS SELECTION GUIDE

PUMP		ALL MODELS							
SPM	1 to 300 strokes/min (adjustable in 1-stroke units)								
Pressure	100 psi maximum discharge pressure								
Viscosity	≈ 50 mPa/cps maximum viscosity								
Materials	PMMA liquid end, fluoro rubber o-ring & valve seat, ceramic check ball								
Model	DCLPW-30R	DCLPW-60R	DCLPW-100R						
Capacity	0.48 gph	0.95 gph	1.42 gph						
Input	PULSE								
Dis Tubing	4x9mm (PVC braided hose)	6x11 mm (PVC braided hose)	6x11 mm (PVC braided hose)						
Dis Tubing	6x8mm (PE)	6x8mm (PE)	6x8mm (PE)						
Suc Tubing	1/4"x 3/8" (PE)	1/4"x 3/8" (PE)	1/4"x 3/8" (PE)						
Model	DCLPW-T-30R	DCLPW-T-60R	DCLPW-T-100R						
Capacity	0.48 gph	0.95 gph	1.42 gph						
Input	TIMER								
Dis Tubing	4x9mm (PVC braided hose)	6x11 mm (PVC braided hose)	6x11 mm (PVC braided hose)						
Dis Tubing	6x8mm (PE)	6x8mm (PE)	6x8mm (PE)						
Suc Tubing	1/4"x 3/8" (PE)	1/4"x 3/8" (PE)	1/4"x 3/8" (PE)						
TANK	PTS-30	PTS-50	PTS-120						
Capacity	7.9 gal	13.2 gal	31.7 gal						
Material	PE	PE	PE						
Seal	EPDM	EPDM	EPDM						
Dimensions	h	d	w	h	d	w	h	d	w
	23.3"	15.3"	13.1"	29.1"	17.4"	17.1"	34.2"	20.6"	20.2"
Features	Mounting pad, foot-valve, injection quill, suction/discharge tubing, level sight-gage, pump cover, drain plug, splash guard, lockable lid								



MURPHY & DICKEY, INC.
930 N. YORK ROAD #205
HINSDALE, IL 60521
630-655-1080
sales@murphyanddickey.com